



WEBER

PRÜFTECHNIK

LWD WEBER
connect



Cables are a thing of the past!

- Wireless connection - no measuring cable
- Printer inside the handheld
- Menu control via colour touchscreen
- Virtual keypad to label the measurements in an easy way
- More than 200 measurements with one charge of the battery
- One mains adapter charges both batteries at the same time
- Maximum charging time: 3 hours
- High-quality coating against corrosion and long-lasting protection against environmental influences

Technical data sheet - LWD WEBERconnect

Handheld:

Dimensions:

Length: 203mm

Width: 108mm

Height: 40-55mm



Equipment:

colour touchscreen without a pen, thermal printer with paper roll for 64 printouts, 4GB SD-card and card slot, GPS module, high-performance battery, backup battery, radio path to load plate with a transmission range up to max. 10m, battery charge indicator, internal storage for thousands of measurements, automatic menu navigation with beep-tone confirmation, three-colour display of the measurement curves, three language series - many languages available, virtual keypad to label the records, energy-saving option, mains adapter with all common worldwide adapters

Loading device

10 kg

Dimensions:

Height: 115mm

Diameter: 235mm

Mass of the falling weight:

10kg

Total weight: 15kg

Drop height approx. 72cm



Equipment:

weight with ball bearing, 17 plate springs, square handle with long support against rolling motion during transport, circular level, index bolt stainless steel as transport lock, galvanised coating

Load plate

Dimensions:

Diameter: 300mm

Plate thickness: 20mm

Total height: 130mm

Weight: 15kg



LWD WEBERconnect
...und alles im
Grünen

Equipment:

Electronic board with acceleration sensor, charging socket and battery, switch with monitoring light, transmitter for radio path up to max. 10m, slots for attaching transport cart, two handles, galvanic coating