

JOINT CUTTERS



NEW - Joint cutter CF-13.2 B

The joint cutter CF-13.2 B is preferably used in landscape gardening or for easy tasks in road construction. Its simple handling and compact size recommend the machine for rental business.

Now available with a new visor!
For precise cuts and and very low in vibration



Optimized heat protection plate for more security and comfort
fixed with screws on both sides under the watertank



Modern design because of a facelift of the machine

The adjustment of cutting depth is regulated by hand wheel, lifting by a low maintenance balance. The operating handle is rubber mounted and especially low in vibration.

The large water container of pressurized water provides the supply of water.

- moderne cyclone air filter for long maintenance rates
- large water container with ergonomic recessed grip
- ring eye for loading
- extendable handle for relocating the machine manually
- adjustable cutting depth indicator and locking brake
- saw blade mounting possible on right or left side



| technical data | CF-13.2 B |
|--------------------------|-----------------------|
| cutting depth | 95 - 170 mm |
| blade-Ø | 300 - 450 mm |
| bore hole of blade | 25,4 mm |
| blade mounting | right or left |
| max. mounting width | 13 mm |
| motor output (net) | 8,7 kW |
| motor type | Honda GX-390 (petrol) |
| motor starter | reversing start |
| cutting depth adjustment | hand wheel |
| feed | manual |
| contents water tank | 23 l |
| dimensions L/W/H | 820/520/870 mm |
| weight | 102 kg |