

JOINT CUTTERS



Joint cutters CF-1020 B and CF-1020 D

Application

- it is preferably used in landscape gardening or for easy tasks in road construction
- its simple handling and compact size recommend the machine for rental business

Features

- large hand wheel for precise cutting depth adjustment
- mounting of saw blade on right or left side
- ergonomically designed and height-adjustable machine handle of low vibrations
- high manoeuvrability due to extra large running wheels (Ø 200 mm)
- high steadiness due to extremely deep balance point

cutting depth up to 200 mm

blade mounting Ø 500 mm

removable water container with extra large filling opening

oil-shortage switch and cyclone filter



| technical data | | CF-1020 B | CF-1020 D |
|--------------------------|---------|-----------------------|--------------------|
| cutting depth | mm | 125 - 200 | 125 - 200 |
| blade-Ø | mm | 350 - 500 | 350 - 500 |
| bore hole of blade | mm | 25,4 | 25,4 |
| blade mounting | lateral | right or left | right or left |
| max. mounting width | mm | 20 | 20 |
| motor output (net) | kW | 8,7 | 7,3 |
| motor type | - | Honda GX-390 (petrol) | Hatz 1B40 (diesel) |
| motor starter | - | reversing start | reversing start |
| cutting depth adjustment | - | hand wheel | hand wheel |
| feed | - | manual | manual |
| contents water tank | l | 28 | 28 |
| dimensions L/W/H | mm | 1290/570/1050 | 1290/570/1050 |
| weight | kg | 123 | 142 |