

**NEW: with larger gripping range**



### EASYGRIP EXG Border Stone Handle

**Small, lightweight, easy to handle but nonetheless ultra-strong!**

EASYGRIP EXG is a mechanical grab suitable for handling parallel, plane and non-conical concrete elements, such as border stones, slabs, block steps and kerb stones.

► The compact and lightweight EASYGRIP EXG can be attached to a carrier (loading crane,

mini-excavator etc.) by means of hoisting belts or chains. Thus just one person is able to operate the grab mechanically.

► The grab comes with two handles and thus is also suitable for a two-man manual operation.

**\*NEW: EXG-MAXI** with larger gripping range and height-adjustable support as standard.

Type <sup>⓪</sup>	Gripping Range* W mm (in)	Inside Height ** E mm (in)	Gripper Length L mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
EXG	0 – 300 (0 – 11¾")	145 – 195 (5¾ – 7½")	235 (9¼")	550 (1,200)	12 (26)	5310.0370
* EXG-MAXI	0 – 400 (0 – 15¾")	165 – 215 (6½ – 8½")	235 (9¼")	600 (1,320)	15 (33)	5310.0392

\*\* depending on gripping range



### Kerb and Strip Stone handle RLSH

The perfect and clever handle for small kerbs and strips. Easy handling features quick, efficient and safe laying.

Lifting and laying of stones in ergonomic posture.

- compact size and und little dead weight
- easy jamming and release by just twisting the handle

► LSH 80 – suitable for kerb and strip stones with a width of 80 mm (3.15 inch)

► LSH 120 – suitable for kerb and strip stones with a width from 60 to 120 mm (from 2.36 to 4.72 inch)

Type	for Width of Stones mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
RLSH-80	80 (3¼")	80 (175)	2,5 (5)	5320.0091
RLSH-120-UNI	60 – 120 (2¼" – 4¾")	80 (175)	3,0 (7)	5320.0092



### Kerb Slab Lifter KSH

For transporting lawn edging stones, slabs, etc. The device grips the slab from underneath while at the same time the gripper bar at the top prevents the slab from slipping off.

► Universally suitable for all kerb slabs up to

400 mm in height and 40 mm to 100 mm thickness.

► We recommend using these in pairs when lifting parts of 1 m in length.

► Galvanised finish

Type	Gripping Range W mm (in)	Inside Height E mm (in)	Gripper Length L mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
KSH <sup>⓪</sup>	40 – 100 (1½ – 4")	170 – 400 (6¾ – 15¾")	50 (2")	60 (130)	1.3 (3)	5320.0080



### Flat Grab FZ

FZ for transport of slabs.

- Narrow grippers turn standing slabs or erect laying slabs.
- No problem to grip even tight standing slabs.
- No damage to the surface of the slabs due to gentle handling with rubber grippers.

► High security by enormous transmission of 5:1.

► A spring tension prevents from unintentional slipping off the clamp.

► Lifting band instead of chain or rope: low dead weight, no squeezing, no hurts.

► Suitable for nearly all kinds of material.

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
FZ	0 – 60 (0 – 2½")	800 (1,760)	6 (13)	5310.0278

\*Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab.

⓪ Durable surface protection by galvanizing

011016 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. No liability accepted for any misprints, mistakes and errors.