



TSZ-UNI

## Concrete Step Handles TSZ

Suitable for handling steps, kerb stones, L-stones, etc. in conjunction with a lifting device. Easily adjustable opening width by means of a spring-loaded bolt.

➤ Considerable inside height  
Conical kerb stones are also gripped securely, as the gripper has an inside height of 185 mm thus being able to grip underneath the conical form.

### Standard Specifications:

- Lifting eye for attaching to crane hook.
- Automatic release for fully automatic switch-over from "full" to "empty".

- Exchangeable profiled rubber seals
- Galvanised finish

**TSZ-UNI-WB-SQ:** Special steelfinger grippers allow for safe installation of roughly-cut ashlar rocks. The steel-finger grippers can be screwed on the clamp (built in or after 2009, order number 5310.0338) in just a few simple steps.

**TSZ-UNI-ET:** Fork sleeve with lifting eye and manual turning device, engaging every 90°. Thus the TSZ-UNI can be picked-up with the fork lift truck tines.



TSZ-UNI-WB-SQ

Type	Gripping Range* W mm (in)	Inside Height E mm (in)	Gripper Length L mm (in)	Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>TSZ-UNI<sup>Ⓞ</sup></b>	50 – 600 (2 – 23 1/2")	185 (7 1/4")	350 (13 3/4")	600 (1,320)	29 (64)	<b>5310.0338</b>
<b>TSZ-MAXI<sup>Ⓞ</sup></b>	850 – 1.100 (33 1/2" – 43")	185 (7 1/4")	350 (13 3/4")	600 (1,320)	30 (65)	<b>5310.0364</b>

### Accessories

Type	Gripping Range* W mm (in)	Inside Height E mm (in)	Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>TSZ-UNI-WB-SQ<sup>Ⓞ</sup></b>	50 – 550 (2 – 21 1/2")	210 (8 1/4")	600 (1,320)	6 (13)	<b>4310.1110</b>
<b>TSZ-UNI-ET<sup>Ⓞ</sup></b>			600 (1,320)	25 (55)	<b>4310.1130</b>
<b>Adjustable Height Stop HVA-FTZ/TSZ</b> for all versions FTZ-UNI/MAXI/MULTI and TSZ-UNI/MAXI. adjustable range approx. 50 – 140 mm (2 – 5 1/2")					<b>4310.0867</b>



TSV

## Concrete Step Handles TSV

Universal handles due to a large adjustable opening range. Suitable for steps, kerbs, L-stones, etc.

### Standard Specifications:

- Lifting eye for attaching to crane hook.
- Semi-automatic – for manual switch over

from "full" to "empty".

- Carrying handle
- Carrying handle turnable by 90° according to the working space.
- Exchangeable rubber grippers
- Galvanised finish

Type	Gripping Range* W mm (in)	Inside Height E mm (in)	Gripper Length L mm (in)	Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>TSV<sup>Ⓞ</sup></b>	70 – 500 (2 3/4 – 19 3/4")	125 (5")	200 (7 3/4")	250 (550)	18 (39)	<b>5310.0130</b>


## Turf Stone Laying Clamp RGV

Laying Clamp for Turf Stones, versatile due to exchangeable adaptors.

- RGV-9/9 fits Turf Stones 60 x 40 cm, hole dim. 9 x 9 cm.
- Installs 1 to 5 units at once.

### Standard specifications:

- Automatic release for fully automatic switch-over from "full" to "empty".
- Lifting eye, handle, turnable by 90°.
- Screwable adaptors.



RGV-9/9

Type <sup>Ⓞ</sup>	Description	Gripping Range W mm (in) depending on adaptors	Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>RGV</b>	Basic unit, without adaptors	ca. 70 – 500 (2 3/4 – 20")	250 (550)	15 (30)	<b>4310.1154</b>
<b>RGV-AS-9/9</b>	Adaptors for 9 x 9 cm		250 (550)	5 (11)	<b>4310.1153</b>
<b>RGV-9/9</b>	Complete unit, RGV+RGV-AS-9/9	300/500 (12 – 20")	250 (550)	20 (44)	<b>5310.0372</b>

\*Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab.

<sup>Ⓞ</sup> Durable surface protection by galvanizing