

# This power pack sure *looks* portable!

Exactly. Why tow a large compressor to the site if you don't need to? The CP hydraulic power pack couldn't be more convenient. For site-to-site transportation, two people can lift it into a van. On-site, the CP power pack can easily be wheeled around by one person.

CP hydraulic power packs are available in petrol, diesel or electrically driven versions, and provide portable power for a long list of applications in the 20-40 lpm/140-172 bar range.

## How are they to operate?

Couldn't be simpler. The thermostatically controlled oil cooler gives fast warm-up and helps prevent the hydraulic oil from overheating. Correct working temperature is achieved within minutes – even during the winter. The variable flow on/off valve enables simple tool change and slow start up. A gauge shows when it's time to change the filter.

## What about fuel consumption?

Many of the power packs are equipped with Power On Demand. This system automatically idles the engine when the tool is not being used and speeds it up when the tool is activated. It saves fuel and keeps noise to a minimum.

The power output provided from a 9 HP CP pack when running a 25-32 kg breaker is equal to operating a 20-25 HP compressor running a 32 kg breaker. Thus fuel and maintenance costs are lower – a good example of the benefits of hydraulic power.

Power pack		PAC P9	PAC P13	PAC P18	PAC P18 Twin	PAC D10	PAC E6 <sup>3)</sup>	PAC E11 <sup>3)</sup>	PAC E11 Twin <sup>3)</sup>
Engine		9 HP Honda petrol	13 HP Honda petrol	18 HP B&S Vanguard petrol	18 HP B&S Vanguard petrol	10 HP Lombardini diesel	5.5 kW / 3x400 V / 16A Electric	11 kW / 3x400 V / 32A Electric	11 kW / 3x400 V / 32A Electric
Weight (incl oil)	kg	72	91	118	123	116	70	130	135
Dimensions (LxWxH)	mm	710x525x585	745x600x705	755x700x720	755x700x720	745x600x705	710x525x585	745x605x705	745x605x705
Oil flow	l/min	20	20-30	20-40	2x20/1x40	20	20	30	2x20/1x40
Max pressure	bar	150	150	145	145	150	150	172	155
Fuel capacity	l	6	6,5	7,2	7,2	5,5	-	-	-
Power on Demand (POD)		YES	YES	NO	YES	NO	NO	NO	NO
Oil control: engine oil		YES	YES	YES	YES	NO	NO	NO	NO
Electric start		NO	NO	YES	YES	YES	YES	YES	YES
Sound power level guaranteed, Lw (2000/14/EC) <sup>1)</sup>	dB(A)	101	101	101	101	-	101	101	101
Sound pressure level, Lp, r=1m (ISO 11203) <sup>1)</sup>	dB(A)	88	89	99	99	-	79	86	86
EHTMA class		C	C/D	C/D/E	C/E	C	C	D	C/E
Part number		1807 0080 33	1807 0110 29	1807 0160 28	1807 0160 45	-	1807 0080 47	1807 0160 47	1807 0160 46
<b>None CE approved version</b>									
Part number <sup>2)</sup>		1807 0080 26	1807 0110 25	1807 0160 34	1807 0160 27	1807 0110 27	-	-	-

Two 4-liter bottles of biodegradable hydraulic oil is included in the delivery of each power pack.

<sup>1)</sup> **Important:** Full details of measurement is available in the Safety and Operating Instruction of the product. It can be found on [www.cpprintshop.com](http://www.cpprintshop.com)

<sup>2)</sup> Not sold within EU

<sup>3)</sup> Electric versions not sold in North America