

Husqvarna Mini-Planer CG 200 S.

Distributed By:



www.onesourcerental.com



Applications.

- An excellent choice for scarifying or texturing both large and small areas and especially for commercial purposes. Also for traffic line removal.

Benefits.

- Unit can be ordered complete with assembled drum and cutters.
- Sturdy steel frame with 7-3/4" (197mm) wide cutting path which minimizes the number of passes needed when scarifying or texturing large surface areas.
- Depth control adjustment wheel is easy to use with limitless settings (wheel includes locking device).
- Automatic reset to the preset cutting depth.
- Adjustable cutting head height control and retractable handle for easy transportation.
- Premium poly V-belt drives power to the drive shaft.
- 1-1/2" diameter vacuum port allows a dust collection device to be attached.

Technical specifications.

CG 200 S 5	4.8 hp*
CG 200 S 9	8 hp*
CG 200 S 2E	2 hp*
Cutting head width, in (mm)	7-3/4 (197)
Max weight, lbs (kg)	164 (75)

*More technical specifications on page 201. *As rated by the engine manufacturer.*

Product specifications.


	E
965152804, CG 200 5, drum only	
965152824, CG 200 5, star cutter*	
965152818, CG 200 5, beam cutter*	
965152806, CG 200 5, tungsten carbide cutter*	
965152823, CG 200 9, drum only	
965152819, CG 200 9, star cutter*	
965152820, CG 200 9, beam cutter*	
965152807, CG 200 9, tungsten carbide cutter*	
965152801, CG 200 2E, drum only	
965152822, CG 200 2E, star cutter*	
965152821, CG 200 2E, tungsten carbide cutter*	

**Includes Mini-Planer with complete head assembly installed.*


Accessories.

P

For 1/2" shaft	
A Star cutter	177826
B Beam cutter	177828
C 6mm tungsten carbide cutters	177830
D 15mm tungsten carbide cutters	187035
Wire brush - 180mm	173084
Cutter spacer	020766
Edger attachment - complete	173065
Drum assembly only	187057
Complete head assembly kits	
E Star cutter head assembly	187031
F Beam cutter head assembly	187032
G 6mm tungsten carbide head assembly	187033
H 15mm tungsten carbide head assembly	187034
I Wire brush head assembly	173092
For 3/4" shaft	
A Star cutter	173086
B Beam cutter	173085
C 6mm tungsten carbide cutters	173087
D 15mm tungsten carbide cutters	178125
Wire brush - 180mm	173084
Cutter spacer	020768
Edger attachment - complete	173065
Drum assembly only	173015
Complete head assembly kits	
E Star cutter head assembly	173089
F Beam cutter head assembly	173090
G 6mm tungsten carbide head assembly	173091
H 15mm tungsten carbide head assembly	178379
I Wire brush head assembly	173092




Star cutter.



Beam cutter.



6mm tungsten carbide cutter.



15mm tungsten carbide cutter.



Star cutter head assembly.



Beam cutter head assembly.



6mm tungsten carbide head assembly.



15mm tungsten carbide head assembly.



Wire brush head assembly.

Scarifying Machine Accessories

Star Cutters

For general cleaning on concrete, removal of epoxy paint, oil, grease, glue or thermoplastic road markings.

2" O.D. x 1/2" I.D. x .125" Thick (51 x 13 x 3mm)

Beam Cutters

For dressing concrete and asphalt surfaces, anti-skid grooving (ramps, garages, farm yards, etc.) and de-scaling of steel decking.

2" O.D. x 5/8" I.D. x .19" Thick (51 x 16 x 5mm)

6mm Tungsten Carbide Cutters

High performance cutters used to modify surface textures on asphalt or concrete.

2" O.D. x 5/8" I.D. x .25" Thick (51 x 16 x 6mm)

15mm Tungsten Carbide Cutters

High performance cutters used to modify surface textures on asphalt or concrete. Can also be used for coating removal.

2" O.D. x 5/8" I.D. x .75" Thick (51 x 16 x 15mm)

Wire Brush

Removes rust, de-scales, cleans shutters and polishes steel. Customer-installed wire brush kit (item no. 173092) includes shaft assembly and six wire brushes.

	NUMBER OF PIECES REQUIRED FOR COMPLETE HEAD ASSEMBLY			
	1/2" Shaft Assembly		3/4" Shaft Assembly	
	Cutters	Spacers	Cutters	Spacers
Star cutter	108	108	144	144
Beam cutter	108	108	96	96
6mm tungsten carbide cutter	88	100	84	92
15mm tungsten carbide cutter	36	92	28	72
Wire brush - 180mm	6		6	

Distributed By:



www.onesourcerental.com



	CG 200 S 5	CG 200 S 9	CG 200 S 2E
Power, hp*	4.8	8	2
Voltage, volts	–	–	115/230
Full load amps	–	–	23@115V/11.5@230V
Cutting head width, in (mm)	7-3/4 (197)	7-3/4 (197)	7-3/4 (197)
Cutting head rpm	1,325	1,325	1,325
Cutting shaft diameter, in (mm)	1/2 (13)	1/2 (13)	1/2 (13)
Dimensions (L x W x H), in (mm)	27 x 39-1/2 x 15-1/2 (686 x 1,003 x 394)	27 x 39-1/2 x 15-1/2 (686 x 1,003 x 394)	27 x 39-1/2 x 15-1/2 (686 x 1,003 x 394)
Weight, lbs (kg)	138 (62)	164 (75)	164 (75)
Read more on page	189	189	189