

ELECTRIC FAN HEATERS



B 2EPB / 3,3EPB



B 5EPB / B 9EPB / B 15EPB / B 22EPB



- Built-in room thermostat
- No oxygen consumption
- No fumes, no odours, no humidity
- Summer-Winter switch for ventilation only
- Low noise
- Automatic reset (except B 9EPB)
- Motor with thermal protection
- Stainless steel heating elements
- Overheat thermostat
- Adjustable heat
- Strong and long lasting steel construction

OPTIONAL ACCESSORIES:



Extension cord
 B 5EPB, B 9EPB - 5 m - **4511.031**
 B 5EPB, B 9EPB - 10 m - **4511.032**
 B 15EPB, B 22EPB - 5 m - **4511.033**
 B 15EPB, B 22EPB - 10 m - **4511.034**



SPECIFICATIONS		B 2EPB	B 3,3EPB	B 5EPB	B 9EPB	B 15EPB	B 22EPB
Heating power	kW	1/2	1,65/3,3	2,5/5	4,5/9	7,5/15	11/22
	Btu/h	3.400-6.800	5.630-11.260	8.530-17.000	15.350-30.700	25.600-51.200	37.530-75.100
	kcal/h	860-1.720	1.430-2.860	2.150-4.300	3.870-7.740	6.450-12.900	9.460-18.900
Air displacement	m ³ /h	184	510	510	800	1.700	2.400
Power supply	V/Hz	230/50	230/50	230/50	400/50	400/50	400/50
Plug (male) from heater side		-	-	400V / 16A / 5P	400V / 16A / 5P	400V / 32A / 5P	400V / 32A / 5P
Rated current	A	8,7	14,5	7,2	13	22	32
Switch pos. 1		OFF	OFF	OFF	OFF	OFF	OFF
Switch pos. 2		fan	fan	fan	fan	fan	fan
Switch pos. 3/4	kW	1,0/2,0	1,65/3,3	2,5/5,0	4,5/9,0	7,5/15	11,0/22,0
Thermostat control		included	included	included	included	included	included
Temperature range	°C	5-35	5-35	5-35	5-35	5-35	5-35
Protection		IP24	IP24	IP24	IP24	IP24	IP24
Packaging dimension (l x w x h)	mm	240 x 220 x 260	280 x 270 x 440	370 x 310 x 390	420 x 330 x 430	370 x 480 x 530	380 x 550 x 630
Net / gross weight	kg	3,7/4,2	5,1/5,7	6,4/6,8	9,3/10,3	15/15,9	22/22,8
Pallet	pcs	75	48	40	24	15	12