

INFRARED OIL HEATERS

XL 9 AND XL 91



XL 9



XL 91



Ventilation of the room is necessary to prevent a deficiency in oxygen supply.



XL 9

PATENTED



XL 91

PATENTED



- ▼ Low noise
- ▼ Infrared heating (short wave)
- ▼ No air flow
- ▼ Electronic flame control with photocell
- ▼ Post-ventilation
- ▼ Oil level indicator
- ▼ Possible connection to an optional room thermostat
- ▼ Oil pump filter, suction filter and inlet filter
- ▼ Snorkel (XL 91)
- ▼ Adjustable direction/Tilting
- ▼ Trolley included

OPTIONAL ACCESSORIES:



Fuel pre-heater
4031.120



Room thermostat
TH5 with cable
3 m - 4150.109
10 m - 4150.112



Digital thermostat
THD with 5 m cable
4150.106
(for XL 91 only)



Manometer
4109.435

SPECIFICATIONS		XL 9		XL 91	
Heating power	kW	29	43	29	43
	Btu/h	99.300	146.900	99.300	146.900
	kcal/h	25.000	37.000	25.000	37.000
Fuel consumption	kg/h	2,3	3,37	2,3	3,37
Fuel autonomy	h	21	14	21	14
Thermostat control		optional TH5		optional TH 5 or THD	
Electric power	kW	0,16		0,19	
Power supply	V	220-240*		220-240*	
Frequency	Hz	50		50	
Rated current	A	0,7		0,7	
Tank capacity	l	60		60	
Product size (l x w x h)	mm	1070 x 700 x 980		710 x 970 x 990	
Box size (l x w x h)	mm	1200 x 750 x 1130		1030 x 750 x 1190	
Net/gross weight	kg	69/85		69/85	
Pallet	pcs	1		1	

* 110 V available